DATASHEET

The extra large Ambu BlueSensor VLC features conductive wet gel and a combination of fast and long-term adhesives for stable signals throughout the monitoring period.

To minimise reactions to sensitive skin, the sponge is covered by a membrane, preventing direct contact between skin and sponge.

Thanks to the thin microporous material, the skin is able to breathe and the electrode remains comfortable to wear over long periods.

Key benefits

- Offset connector mitigates the impact on signal quality from external forces like pulling of lead wires and pressure on electrodes
- Offset connector allows the user to connect and disconnect the lead wire without applying pressure to the patient or the sensor area, which reduces the risk of gel spreading and adhesive detachment from skin
- Conductive wet gel lowers skin impedance effectively and immediately
- Wet gel optimises contact between skin and electrode
- Combination of fast and long-term adhesives secures fixation and a stable signal
- Thin microporous backing material allows the skin to breathe
- Ag/AgCl sensor ensures stable signal quality
- Visible release liner can help prevent medical accidents for both users and patients

Ambu® BlueSensor VLC

ECG Electrode Single use





Wet gel



Microporous backing



Double ring adhesive



Silver sensor



Breathable backing






SPECIFICATIONS

Dimensions			
Electrode size (length x width in mm)	72 x 68		
Skin contact size (diameter in mm)	68		
Adhesive area (in mm²)	3377		
Sensor			
Sensor material	Silver/silver chloride (Ag/AgCl)		
Gel system	Wet gel		
Gel area/measuring area (in mm²)	254		
Electrical data (ANSI/AAMI)			
AC impedance - typical	550 Ω		
DC offset voltage - typical	3.6 mV		
Defibrillation overload recovery - typical	10.16 mV		
Rate of change of polarisation potential - typical	- 0.1 mV/s		
Combined offset instability and internal noise	4.6 μV		
Bias current tolerance (over 8 hours)	4.9 mV		

Environment				
Electrode is not made with natural rubber latex				
Wire is not made with natural rubber latex				
Packaging is PVC-free				
X-ray & MRI				
Radiolucent	No			
MR Conditional	No			
Shelf life				
Opened pouches	1 month			
Unopened pouches*	15 months			

^{*}from date of production.

CONNECTORS



S = Stud

MATERIALS

Electrode	
Bio-compatible	Yes
Sponge	Polyurethane foam/microporous (non woven rayon)
Backing material	Microporous tape (non woven rayon) and (blue) polyvinyl chloride film
Skin adhesive	Acrylate
S Connector (stud)	Nickel-plated brass
Release liner	Polyester/polyethylene film (PET/PE)

Packaging	
Pouch (outer/ middle/inner layers)	Polyester/ Aluminium/ Polyethylene
Boxes	Cardboard
Options	
Non-wired connectors	S
Precaution	
Single use only	

AVAILABLE CONFIGURATIONS*

Reference number	Units/liner	Units/pouch	Units/inn	er box Units/o	outer box
VLC-00-S/4	1	4	500	1000	
VLC-00-S/10	1	10	500	1000	
VLC-00-S/25	1	25	500	1000	
		VLC-00-S	■ Product	■ Wire length	■ Connector

^{*}some configurations may not be available worldwide.

Ambu

Ambu Australia Pty Ltd

Unit 5, 2 Daydream Street, Warriewood NSW 2102 Tel: 1300 233 118 aussales@ambu.com www.ambuaustralia.com.au

