

## DATASHEET

---

The radiolucent Ambu BlueSensor BR features a skin-friendly solid gel that provides stable signal quality in neonatal monitoring.

The soft cloth backing material makes the electrode comfortable to wear over long periods. The BR electrode is only available with preattached lead wires (colour-coding optional).

### Key benefits


- Skin-friendly solid gel supports the quality of the signal
- Soft cloth backing material allows the skin to breathe
- Extra small size is suitable for neonates
- Radiolucency allows the electrode to remain on the patient during X-ray procedures

# Ambu® BlueSensor BR

ECG Electrode  
Single use



Solid gel




Cloth backing



Silver sensor



Radiolucent



Breathable backing

**BlueSensor**

**Ambu**

## SPECIFICATIONS

### Dimensions

Electrode size (length x width in mm)	28 x 20
Skin contact size (length x width in mm)	28 x 20
Adhesive area (in mm <sup>2</sup> )	503

### Sensor

Sensor material	Silver/silver chloride (Ag/AgCl)
Gel system	Solid gel
Gel area/measuring area (in mm <sup>2</sup> )	503

### Electrical data (ANSI/AAMI)

AC impedance - typical	700 Ω
DC offset voltage - typical	3.3 mV
Defibrillation overload recovery - typical	17.85 mV
Rate of change of polarisation potential - typical	-0.38 mV/s
Combined offset instability and internal noise	2 μV
Bias current tolerance (over 8 hours)	7.2 mV

## MATERIALS

### Electrode

Bio-compatible	Yes
Backing material	Non-woven polyester cloth
Sensor carrier	Carbon-filled polyvinyl chloride
Skin adhesive	Solid gel
Lead wire core	Carbon
Lead wire insulation	Polyvinyl chloride (PVC)
Lead wire connector	Brass/polypropylene (PP)
Release liner	Siliconised polyester film

### Environment

Electrode is not made with natural rubber latex
Wire is not made with natural rubber latex
Packaging is PVC-free

### X-ray & MRI

Radiolucent	Yes
MR Conditional	No

### Shelf life

Opened pouches	1 month
Unopened pouches *	18 months

\*from date of production

### Packaging

Pouch (outer/middle/inner layers)	Polyester/ Aluminium/ Polyethylene
Boxes	Cardboard

### Options

Pre-wired connectors	A, F, K
----------------------	---------

### Precaution

Single use only

## CONNECTORS



A = 4 mm connector



K = 1.5 mm connector



F = 3 mm connector

## AVAILABLE CONFIGURATIONS\*

Reference number**	Units/liner	Units/pouch	Units/inner box	Units/outer box
BR-50-K/3	3	3	600	1200
BR-50-K/US/3	3	3	600	1200
BR-50-A/12	3	12	600	1200
BR-50-K/12	3	12	600	1200
BR-50-K/EU/12	3	12	600	1200
BR-80-A/12	3	12	600	1200
BR-80-K/12	3	12	600	1200
BR-100-F/C4/4	4	4	600	1200
BR-100-F/C6/6	6	6	600	1200
BR-100-K/C3/3	3	3	600	1200
BR-100-K/C4/4	4	4	600	1200
BR-100-K/C6/6	6	6	600	1200
BR-100-K/12	3	12	600	1200
BR-170-K/C4/4	4	4	600	1200
BR-170-K/C6/6	6	6	600	1200

BR-50-A ■ Product ■ Wire length ■ Connector

\*some configurations may not be available worldwide

\*\*coloured lead wires

EU: black, red, yellow

US: black, green, white

C3: red, yellow, green

C4: red, yellow, green, black

C6: red, yellow, green, brown, black, purple

# Ambu

**Ambu Australia Pty Ltd**  
Unit 5, 2 Daydream Street  
Warriewood  
NSW 2102  
Tel: 1300 233 118  
aussales@ambu.com  
www.ambuaustralia.com.au

**CE** US: Rx only