

## DATASHEET

The extra small radiolucent Ambu BlueSensor BRS has been specially developed for babies and newborns. The electrode features a skin-friendly solid gel that ensures stable signal quality.

The soft cloth backing material makes the electrode comfortable to wear over long periods. The BRS is only available with preattached lead wires (colour-coding optional).

### Key benefits

- Skin-friendly solid gel supports the quality of the signal
- Soft cloth backing material allows the skin to breathe
- Extra small size is suitable for neonates
- Radiolucency allows the electrode to remain on the patient during X-ray procedures


# Ambu® BlueSensor BRS

ECG Electrode

Single use



Solid gel




Cloth backing



Silver sensor



Radiolucent



Breathable backing

**BlueSensor**

**Ambu**

## SPECIFICATIONS

### Dimensions

Electrode size (length x width in mm)	16 x 19
Skin contact size (length x width in mm)	16 x 19
Adhesive area (in mm <sup>2</sup> )	269

### Sensor

Sensor material	Silver/silver chloride (Ag/AgCl)
Gel system	Solid gel
Gel area/measuring area (in mm <sup>2</sup> )	269

### Electrical data (ANSI/AAMI)

AC impedance - typical	560 Ω
DC offset voltage - typical	4.6 mV
Defibrillation overload recovery - typical	19.67 mV
Rate of change of polarisation potential - typical	-0.39 mV/s
Combined offset instability and internal noise	3.3 μV
Bias current tolerance (over 8 hours)	10.1 mV

## MATERIALS

### Electrode

Bio-compatible	Yes
Backing material	Non-woven polyester cloth
Sensor carrier	Carbon-filled polyvinyl chloride
Skin adhesive	Solid gel
Lead wire core	Carbon
Lead wire insulation	Polyvinyl chloride (PVC)
Lead wire connector	Brass/polypropylene (PP)
Release liner	Siliconised polyester film

### Environment

Electrode is not made with natural rubber latex  
 Wire is not made with natural rubber latex  
 Packaging is PVC-free

### X-ray & MRI

Radiolucent	Yes
MR Conditional	No

### Shelf life

Opened pouches	1 month
Unopened pouches *	18 months

\*from date of production

## CONNECTORS



A = 4 mm connector



K = 1.5 mm connector

### Packaging

Pouch (outer/middle/inner layers)	Polyester/ Aluminium/ Polyethylene
Boxes	Cardboard

### Options

Pre-wired connectors	A, K
----------------------	------

### Precaution

Single use only

## AVAILABLE CONFIGURATIONS\*

Reference number**	Units/liner	Units/pouch	Units/inner box	Units/outer box
BRS-50-A/12	3	12	600	1200
BRS-50-K/12	3	12	600	1200
BRS-50-K/C3/3	3	3	600	1200
BRS-50-K/EU/12	3	12	600	1200
BRS-50-K/EU/3	3	3	600	1200
BRS-50-K/US/3	3	3	600	1200

BRS-50-A ■ Product ■ Wire length ■ Connector

\*some configurations may not be available worldwide

\*\*coloured lead wires

EU: black, red, yellow

US: black, green, white

C3: red, yellow, green

# Ambu

### Ambu Australia Pty Ltd

Unit 5, 2 Daydream Street  
 Warriewood  
 NSW 2102  
 Tel: 1300 233 118  
 aussales@ambu.com  
 www.ambuaustralia.com.au

CE US: Rx only