KEY BENEFITS

All-in-one sampling solution.

Simplifies workflow.

Closed-loop system helps reduce risk of contamination and sample loss.

World's first single use bronchoscope with bioplastic handle.

Improves patient safety and simplifies sampling workflow

Streamline workflow with **Ambu® aScope™** 4 Broncho Regular Sampler Set, an all-in-one, closed-loop sampling system. This innovative solution is delivered sterile, ready when you are, and comes with all the critical sampling components you need for BAL and BW procedures.

Simplifies the sampling process

The Sampler Set improves workflow efficiency with plug-and-play features that are intuitive to set up and easy to connect to the **Ambu® aView™** 2 Advance portable monitor. Unlike other solutions, the Sampler Set also features a vacuum bypass that enables you to change between suction and sampling without a suction tube switch, which further simplifies procedures.

Protects samples from start to finish

The single-use, sterile closed-loop system reduces the risk of sample loss ensuring timely diagnostics and sample quality throughout the procedure. The closed-loop system minimises the risk of sample contamination and exposure, thereby enhancing the safety of both patients and clinicians.

Ambu[®] aScope[™] 4 Broncho Regular Sampler Set The breakthrough all-in-one sampling solution





SPECIFICATIONS

| Ontion sustain | |
|---|--|
| Optical system | 85° |
| Field of view Direction of view | 0° (forward viewing) |
| Depth of field | 6 - 50 mm |
| Illumination method | 2 LEDs |
| Insertion portion | |
| Bending section | 180° up, 180° down |
| Insertion cord diameter | 5.0 mm (0.20") |
| Distal tip diameter | 5.4 mm (0.21") |
| Maximum diameter of insertion portion | 5.5 mm (0.22") |
| Minimum endotracheal tube size (inner diameter) | 6.0 mm |
| Minimum double lumen tube size (inner diameter) | 41 Fr |
| Working length | 600 mm (23.6") |
| Channel | |
| Average inner diameter | 2.2 mm (0.087") |
| Minimum instrument channel width | 2.0 mm (0.079") |
| Suction connector | |
| Connecting tube with female interface | ID = Ø7 ± 1 mm |
| Connecting tube with male interface Applicable when suction adapter is used | OD = Ø7 ± 1 mm |
| Sample container | |
| Sample container volume | 30 ml |
| Storage | |
| Temperature** | 10 - 25 °C |
| | |
| Relative humidity | 10 - 85 % |
| Relative humidity Atmospheric pressure | |
| Atmospheric pressure | 10 - 85 % |
| Atmospheric pressure Transportation | 10 - 85 % |
| Atmospheric pressure Transportation Temperature | 10 - 85 % 50 - 106 kPa |
| Atmospheric pressure Transportation Temperature Relative humidity | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure | 10 - 85 % 50 - 106 kPa -10 - 55 °C |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure Operating environment | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % 50 - 106 kPa |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure Operating environment Temperature | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % 50 - 106 kPa 10 - 40 °C |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure Operating environment Temperature Relative humidity | 10 - 85 % 50 - 106 kPa -10 - 55 ℃ 10 - 95 % 50 - 106 kPa 10 - 40 ℃ 30 - 85 % |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure Operating environment Temperature Relative humidity Atmospheric pressure Atmospheric pressure | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % 50 - 106 kPa 10 - 40 °C 30 - 85 % 80 - 106 kPa |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure Operating environment Temperature Relative humidity Atmospheric pressure Atmospheric pressure Atmospheric pressure Atmospheric pressure Atmospheric pressure | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % 50 - 106 kPa 10 - 40 °C 30 - 85 % 80 - 106 kPa |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure Operating environment Temperature Relative humidity Atmospheric pressure Atmospheric pressure Atmospheric pressure Atmospheric pressure Atmospheric pressure Atmospheric pressure Attitude Sterilisation | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % 50 - 106 kPa 10 - 40 °C 30 - 85 % 80 - 106 kPa ≤ 2000 m |
| Atmospheric pressure Transportation Temperature Relative humidity Atmospheric pressure Operating environment Temperature Relative humidity Atmospheric pressure Operating environment Temperature Relative humidity Atmospheric pressure Altitude Sterilisation Method of sterilisation | 10 - 85 % 50 - 106 kPa -10 - 55 °C 10 - 95 % 50 - 106 kPa 10 - 40 °C 30 - 85 % 80 - 106 kPa ≤ 2000 m |

ORDERING SPECIFICATIONS

| ltem no. | Product name | Quantity |
|-----------|---|----------|
| 477501000 | Ambu® aScope™ 4 Broncho Regular Sampler Set | 5 |
| 480500000 | Ambu® aScope™ BronchoSampler 60 SC | 10 |

* There is no guarantee that accessories selected solely using this minimum instrument channel width will be compatible in combination. ** Storage under higher temperatures may impact shelf life.



Learn more about Ambu's sustainability initiatives: https://www.ambu.com/endoscopy/single-use-endoscopy/environment



Ambu Australia Pty Ltd | Ambu New Zealand Pty Ltd Unit 5, 2 Daydream Street, Warriewood, NSW 2102 Tel (AUS): 1300 233 118 | Tel (NZ): 0800 804 079 Email: aussales@ambu.com Web: www.ambuaustralia.com.au Always read the Instructions for Use. These products are only available for sale to healthcare professionals.

©2024 Ambu Australia Pty Ltd Ambu[®] is a registered trademark. aScope[™] and aView[™] are a trademark of Ambu.



The ergonomic and lightweight handle is designed to give you a firm and comfortable grip



Switch from suctioning to sampling by the flip of a switch



Easily close lid to seal retrieved sample

CE 2797